

FEATURES		EFI.02	EFI.05	EFI.06	EFI.07
Earth fault trip current (values are customer defined)	Single current value	✓			
	Up to 4 values (jumpers selectable)		✓	✓	✓
Min. Fault Duration (Delay) (values are customer defined)	Single time value	✓			
	Up to 4 values (jumpers selectable)		✓	✓	✓
Visual Fault Signalling (main unit)	Flashing ultra-bright single LED	✓	✓		✓
	Flashing ultra bright LED LAMP with red lens			✓	
Power Supply	Self-powered by internal lithium battery (10 years lifetime)	✓	✓	✓	✓
Remote Fault Signalling (SCADA)	1NO + 1NC relay momentary contact (500ms)	(o)	✓	✓	✓
	1NO + 1NC relay permanent contact	(o)	(o)	(o)	(o)
Automatic RESET after time delay (values are customer defined)	Single time value	✓			
	Up to 4 values (jumpers selectable)		✓	✓	✓
Mains 230Vac RESET		✓	✓	✓	✓
Pushbutton (manual) RESET		✓	✓	✓	✓
Remote RESET by NO contact (SCADA) or remote pushbutton			✓	✓	✓
Installation	Wall mount	✓	✓	✓	
	Panel mount DIN 48 x 96				✓
Load current RESET			(o)	(o)	(o)
Connection for External Indicator		(o)	(o)	(o)	(o)

✓ Feature present

(o) Option